

Fire detection and evacuation solutions that save lives.

## Intrinsically Safe Sounder, Beacon and Sounder/Beacon

## **Features**

- Input Overload and Reverse Current Protection
- End of Line Resistor Certified
- ATEX and IECEx approval
- 2 x M20 clearance gland knockouts
- Auto Synchronised Sound Output (exc. Beacon)

## **Description**

The Intrinsically Safe range of products includes the compact I.S. Sounder, I.S. Beacon and I.S. Sounder / Beacon.

The range is suitable for all intrinsically safe signalling applications including fire, security and process control. Approvals include ATEX and IECEx and GOST-R for Zone 0 applications and FM approval for Class I Division 1 and Class I Zone 0 applications.

The I.S. Beacon optimises the effectiveness of its six high output LEDs via a prismatic lens design.

The I.S. combined Sounder and Beacon requires only one Zener barrier or galvanic isolator to run both sounder and beacon or alternatively the unit can be operated as individual signals.

Power to the I.S. range should be via a certified zener barrier or galvanic isolator whose output parameter is no greater than, Uo=28v dc, Io=93mA,and Po=660mw. The beacon is internally input overload and reverse polarity protected and is end of line monitoring resistor certified.



Intrinsically Safe Range

Item Numbers			
205-0111	I.S. Sounder Beacon Red Body, Red Lens		
205-0115	I.S. Sounder Beacon Red Body, Amber Lens		
205-0116	I.S. Sounder Beacon Red Body, Clear Lens		
205-0114	I.S. Sounder Red Body		
208-0201	I.S. Beacon Red Body, Red Lens		
208-0202	I.S. Beacon Red Body, Amber Lens		
208-0203	I.S. Beacon Red Body, Clear Lens		

Specifications					
	Beacon	Sounder	Sounder/Beacon		
Voltage Range	16-28Vdc v	28Vdc via Zener barrier or galvanic isolator			
Nominal Current Consumption	25mA at 24V DC	25mA at 24V DC	30mA at 24V DC		
Flash Modes	-	double flash at 2Hz and 1Hz			
Effective Intensity Candela	-	23cd	23cd		
Sound Output (nominal) at 1m +/- 3dB - Tone 2a	100dB(A)	-	100dB(A)		
Number of Tones	49	-	49		
Temperature Range	-40 to +60°C				
Protection Rating	IP65				
Body Colours	Red				
Lens Colour	- Red, Amber, Clear				

A **Halma** company