

Intelligent Manual Call Point

Features

- Suitable for Flush or Surface Mount Application
- Plug E-Z Fit Connector
- Easy Access
- Front Reset Mechanism
- 170° viewable LED
- Ergonomic Reset Key
- Integral Short Circuit Isolator
- Continuity Link for Cable Insulation Testing

Description

The Intelligent Manual Call Point is intended for indoor use and has been designed to operate on a loop of intelligent addressable fire detection devices. An alarm is initiated by pressing the resettable element. The manual call point signals to the Ampac fire control panel using an interrupt feature within the digital protocol.

An alarm status is indicated through the rotation of the resettable element, displaying yellow and black indication bars and a solid red LED. The manual call point can be easily reset from the front using the reset key supplied.

Protocol Compatibility

The Intelligent Manual Call Point will operate with the Ampac control panel using the digital XP95 or Discovery protocol which is switch selectable at the commissioning stage.

Operating Principles

The address of each call point is set at commissioning stage by means of integral DIL switch.

A solid red alarm LED is provided on the manual call point. This LED is controlled independently of the call point by the Ampac fire control panel. When configured as a Discovery device, the LED will flash yellow if there is a fault and flash green when the device is polled. Once activated, the Intelligent Manual Call Point can be reset by inserting the reset key into the front facing LED, turning clockwise until a positive click and reset occurs.

The Intelligent Manual Call Point incorporates a short circuit isolator which will ensure its operation in the event of a short circuit fault on the detection loop cabling. The isolator operation is indicated by a solid yellow LED.

Installation time is reduced by use of a removable terminal block which fits neatly into the back of the manual call point.

Item Numbers

Intelligent Manual Call Point with Isolator
Transparent Cover



Intelligent Manual Call Point

Specifications

Supply Voltage	17-35V DC
Quiescent Current	100µA at 24V DC
Alarm Current	4mA at 24V DC
Dimensions	(H x W x D)
MCP	90mm x 90mm x 26mm
MCP inc back box	90mm x 90mm x 63mm
Material	Fire retardant polycarbonate
Operating Temperature	-40°C to +70°C
Humidity	0 – 95% RH non-condensing
EMC Directive	2004/108/EC
IP Rating	44 (indoor use)
Weight	180g

To provide additional protection against accidental operation, a transparent hinged cover is available which can be fitted to the Manual Call Point.

For further details on the isolator refer to PDS201-9001



LPCB (EN54-11&17)	SAI Global (AS7240-11)
SA5900-908AMP	4105-2005
44251-175	4105-2003

WORLD LEADER OF INNOVATIVE SOLUTIONS
IN FIRE DETECTION AND ALARM SYSTEMS

AMPAC
ADVANCED WARNING
SYSTEMS