

Fire detection and evacuation solutions that save lives.

FireView Portable Detector Test Kit

Features

- All-in-One Fire Detector Test Set
- Fast, Simple and Efficient Operation
- Built in Smoke Extraction Fan
- No Residue
- Built in Battery Charger
- Detector Removal Tool
- Electronically Operated via Key Fob
- LED Display Panel



Description

FireView provides a unique all-in-one solution for reliable testing of both smoke and heat fire detectors.

To negate the risk of using ladders and scaffolding, the test kit has been designed to aid technicians from floor level during the service and maintenance of fire detection systems.

FireView can also be used during the system commissioning process to ensure the detection operates to the correct parameters and system design.

FireView contains sustainable smoke generation system which eliminates the need for additional spray purchases and prevents deterioration of detector sensitivity by negating residue build up within the smoke detector. The fan attached to the head of the inspection pole removes any residual smoke remaining inside the detector speeding up the testing process.

Each kit is provided with a universal detector removal tool suitable for occasional site works. A more robust tool, be-spoke to the Apollo XP95 & Discovery range of detectors is also available.

Application

- Point Type Smoke Detectors
- Point Type Rate-of-Rise & Fixed Temp Heat Detectors
- Addressable and Conventional Systems



10M Extension Pole Retracted = 1.8M Weight 3.6kg

Specifications	
Testable Detectors	Heat: Rate of Rise; Fixed Temperature Smoke: Ionization; Photoelectric
Test Capacity (full charge)	Approx. 150 Heat Detectors (approx. max temp 90°C) Approx. 300 Smoke Detectors
Smoke Tests	Approx. 1000 tests per 100ml bottle
Head Dimensions	150mm Ø
Extension Pole Length	Retracted 1.3M - Extended 3M
Weight	2.3kg
Operating Temp	Approx. 0°C - 40°C
Storage Temp	Approx10°C - 40°C
Relative Humidity	Approx. 0 - 85%, No Frost
Battery	14.8v Li-ION Battery Pack
Charging Time	Full charge consumes approx. 5 hours
Charger	Input: AC 100 - 240v, 50 - 60 Hz, 0.5A Output: DC 12V2A

Item Numbers	
4112-1012	FireView Portable Fire Detector Test Kit
4112-1007	Smoke Oil (100ml)
4112-1008	FireView 6M Extension Pole
4112-1009	FireView 10M Extension Pole
4112-1010	FireView Removal Tool Apollo Smoke Detectors
4112-1011	FireView Removal Tool Apollo Heat Detectors
4112-1013	FireView Replacement Head Unit

Note, battery lifespan typically 2-3 years depending on use. Ampac do not supply replacement batteries, these should be sourced locally.

Not recommended for use with high temp heat detectors.