## Certificate No.: 2531-CPR-CSP10885



### **CERTIFICATE OF CONSTANCY OF PERFORMANCE**

Issued by DBI Certification, notified body No. 2531.

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

### 55000-122AMP Series 65 Conventional Class A1R Heat Detector

The product fulfils the essential characteristic:

See Annex 1

Intended use: Applications related to automatic fire alarm systems

Placed on the market under the name or trade mark of:

Ampac Pty Ltd 7 Ledgar Road, Balcatta, 6021, Australia

and produced in the manufacturing plant:

Apollo Fire Detectors Limited
36 Brookside Road, Havant, Hampshire, PO9 1JR, UK

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standards

EN 54-5:2000/A1:2002 : Fire detection and fire alarm systems - Part 5: Heat detectors - Point detectors

under system 1 for the performance set out in this certificate are applied and that the performance of the construction product is assessed to remain constant.

The attached annexes form part of this certificate.

Date of issue: 2019-10-24.

This certificate will remain valid as long as neither the harmonized standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly unless suspended or withdrawn by the notified product certification body.

This certificate was first issued 2019-10-24.

Merete Poulsen Responsible for evaluation Allan Laursen
Responsible for certification decision

DANAK Prod. Reg. Nr. 7023

## Certificate No.: 2531-CPR-CSP10885





Annex 1

### **EXTENT**

### Type:

55000-122AMP Series 65 Conventional Class A1R Heat Detector

#### Bases:

45681-200AMP Series 60/65 Mounting Base

45681-201AMP Series 60/65 Diode Mounting Base

45681-245AMP Series 65 Relay Mounting Base

45681-246AMP Series 65 Auxiliary Mounting Base

45681-247AMP Series 65 EOL 12 Volt Mounting Base

45681-248AMP Series 65 EOL 24 Volt Mounting Base

### Note:

1. Meets the requirements of EN54: Part 5 - Class A1R

### **Performance**

Faceutial above stavistics	Clauses in FN F4 F-2000		Doufoumoneo
Essential characteristics	Clauses in EN 54-5:2000		Performance
Nominal activation	4.2, 4.3, 5.2 to 5.6, 5.8, 6.1, 6.2	2	Pass
conditions/Sensitivity, Response	(6.1 only Suffix S det./6.2 only Suffix		
delay (response time) and	R det.)		
Performance under fire conditions			
Operational reliability	4.4 to 4.11		Pass
Tolerance to supply voltage	5.7		Pass
Durability of operational reliability	5.9, 5.10		Pass
and response delay; temperature			
resistance			
Durability of operational reliability;	5.14 to 5.17		Pass
vibration resistance			
Durability of operational reliability;	5.11, 5.12		Pass
humidity resistance			
Durability of operational reliability;	5.13		Pass
corrosion resistance			
Durability of operational reliability;	5.18		Pass
electrical stability			

# Certificate No.: 2531-CPR-CSP10885





Annex 2

### **TEST DOCUMENTATION**

Accredited Laboratory	Report no.	Date
BRE	P100476-1001 Issue: 1	30 March 2016
VdS	BMA 00018	3 March 2000

### **TECHNICAL BASIS**

File Number	Title
55000-122 45681-200 45681-201 45681-245 45681-246 45681-247 45681-248	Build Standard

