# Certificate No.: 2531-CPR-CSP10928



## **CERTIFICATE OF CONSTANCY OF PERFORMANCE**

Issued by DBI Certification, notified body No. 2531.

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

### 55000-620AMP XP95 Analogue Addressable Optical Smoke Detector

The product fulfils the essential characteristic:

See Annex 1

Intended use: Applications related to automatic fire alarm systems

Placed on the market under the name or trade mark of:

**Ampac Pty Ltd** 

7 Ledgar Road, Balcatta, 6021, Western Australia

and produced in the manufacturing plant:

Apollo Fire Detectors Limited
36 Brookside Road, Havant, Hampshire, PO9 1JR, UK

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standards

EN 54-7:2000/A1:2002/A2:2006 : Fire detection and fire alarm systems - Part 7: Smoke detectors - Point detectors using scattered light, transmitted light or ionization

under system 1 for the performance set out in this certificate are applied and that the performance of the construction product is assessed to remain constant.

The attached annexes form part of this certificate.

Date of issue: 2019-10-24.

This certificate will remain valid as long as neither the harmonized standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly unless suspended or withdrawn by the notified product certification body.

This certificate was first issued 2019-10-24.

Merete Poulsen
Responsible for evaluation

Allan Laursen Responsible for certification decision



# Certificate No.: 2531-CPR-CSP10928





Annex 1

## **EXTENT**

### Type

55000-620AMP XP95 Analogue Addressable Optical Smoke Detector

#### Bases:

45681-209AMP XP95/Discovery standard deep mounting base 45681-210AMP XP95 mounting base

### Note:

1. Certified with Apollo Discovery, XP95, and S90 digital communication protocols that have been configured for the Discovery optical smoke detectors in accordance with manufacturer's instructions.

### Performance

Essential characteristics	Clauses in EN 54-7:2000	Performance
Nominal activation	4.8, 5.2, 5.3, 5.4, 5.6, 5.7, 5.18	Pass
conditions/Sensitivity, Response		
delay (response time) and		
Performance under fire conditions		
Operational reliability	4.2 to 4.7, 4.9 to 4.11	Pass
Tolerance to supply voltage	5.5	Pass
Durability of operational reliability	5.8, 5.9	Pass
and response delay; temperature		
resistance		
Durability of operational reliability;	5.13 to 5.16	Pass
vibration resistance		
Durability of operational reliability;	5.10, 5.11	Pass
humidity resistance		
Durability of operational reliability;	5.12	Pass
corrosion resistance		
Durability of operational reliability;	5.17	Pass
electrical stability		



# Certificate No.: 2531-CPR-CSP10928





Annex 2

## **TEST DOCUMENTATION**

Accredited Laboratory	Report no.	Date
BRE	TE-P112845-1001 Issue: 1	23 October 2018
BRE	SW-P112845-1001 Issue: 1	31 October 2018
LPC	TE 82647	July 1993
LPC	TE 82952	September 1994
LPC	TE 83810	October 1993
LPC	TE 84571	June 1994
LPC	TE 84654	June 1994
LPC	TE 93332	13 September 1999
BRE	TE 205437	22 February 2002
BRE	TE288681 Issue: 1	19 December 2016

## **TECHNICAL BASIS**

	File Number			Title
55000-620 45681-209 45681-210		Build Standa Build Standa Build Standa	nrd	

