

Fire detection and evacuation solutions that save lives.

## Ceiling Speaker with ABS Grille

## **Features**


- 200mm low profile design
- Tuned PA driver designed to meet fire standards
- Excellent speech intelligibility
- Fire resistant ABS safety cover
- High quality speaker driver
- · Compression glands supplied
- · One-shot 'snap-fit' mounting




Designed to meet the requirements of evacuation and occupant warning paging systems. This high efficiency speaker and transformer combination ensures high SPL, wide frequency response, superior speech intelligibility and reproduction for critical fire system applications. The ceiling mount speaker is certified to the AS ISO7240.24 standard for fire & evacuation announcements in buildings.

Each speaker is fitted with a fire retardant speaker/ transformer safety cover, cable glands and terminal blocks for easy on site termination. The speaker utilises the One-Shot 'snap fit' mounting system.

## **Dimensions**





Item Numbers		
4113-1064	Ceiling Speaker 200mm White ABS Grille	
4113-1065	Ceiling Speaker 200mm Black ABS Grille	
4113-1065	Ceiling Speaker 200mm Black ABS Grille	



Specifications	
Rated Noise Power	5 Watts (100V line)
Power Taps & Impedance (100V line)	0.33W (30kΩ), 0.66W (15kΩ), 1.25W (8kΩ), 2.5W (4kΩ), 5W (2kΩ)
Sensitivity	94dB (1W @ 1m), 82dB (1W @ 4m)
Maximum Sound Pressure Level	100dB (5W @ 1m), 88dB (5W @ 4m)
Frequency Response	100Hz-15kHz, 500-4kHz ±5dB
Coverage Angle (- 6dB)	500Hz: > 180°, 1000Hz: 170°, 2000Hz: 90°, 4000Hz: 60°
Environmental Type	A (for indoor applications as per standard)
Speaker Component	200mm (8") paper cone speaker
Mounting Hole	246mmØ
Mounting Method	6 x plastic spring loaded clip
Line Monitoring	Yes, 22µF bipolar capacitor
Applicable Cable	2.5mm² (14AWG) max conductor area
Connection	4 way screw terminal
Finish	White or black flame retardant ABS grille (Taitalac 8540T)  Clear Flame retardant ABS spring clips (Makrolon 6557)  Red flame retardant ABS transformer dome cover (Starex VH-0800)
Dimensions	265mm Ø x 108mm D
Weight	1.25 kg

A **Halma** company