

Rapid Bracket[®]

Void Detector Holder

Rapid Bracket[®] has been designed for quick installation straight from the box.

Compatible with most ceiling types and a large variety of detectors, Rapid Bracket[®]'s ultra-fast installation time reduces labour costs significantly and eliminates the need for unsightly access hatches.

Suits Various Detectors ✓

Easy Removal & Installation ✓

Simplifies Maintenance ✓

Easy to Setup ✓

Lightweight ✓



For the full range of solutions visit
the Ampac website www.ampac.net



Rapid Bracket®

Rapid Bracket® is a Void Detector Holder.

It allows the easy installation and future maintenance of detectors in inaccessible or hard to reach ceiling spaces. The Rapid Bracket® eliminates the need for unsightly access hatches, leaving a sleek aesthetically pleasing finish.

Constructed from ultra high heat resistant engineering polymers and light-weight anodized aluminium, the Rapid Bracket® weighs just 1.2kg in its tallest form.

The clever clamping design allows the Rapid Bracket® to be used in ceiling thicknesses ranging from 8mm to 32mm, and gives the additional ability to be back blocked for some of those lighter duty ceilings or ceiling tiles.

- Simple click locking assembly.
- Engineered dimensional components for a balanced device.
- Screwless base design for quick installation.
- Engineered polymer components with high heat tolerance.
- Safety lanyard for faceplate.
- Easy clip on detector holder.



Technical Information:

Cut Out Size	165mm
Installation Height	550mm to 3000mm
Installation Material Thickness	8mm to 32mm
Weight	1.20kg
Material	Anodized Aluminium (Tubes) PA6, PBT-GF (Base) PBT-GF (Detector Holder)
Cover Plate Finish	UV Resistant ABS, White
NCC Compliant	Yes
Recyclable	Yes, Code 7
Patented	Yes

For more information on Ampac's range of fire detection and evacuation solutions visit www.ampac.net