

Fire detection and evacuation solutions that save lives.

ABS Ancillary Interface Enclosure

- ✓ Supports Ampac Range of Interface Devices
- ✓ General Purpose Fire System Applications
- ✓ Cable Entry Knockouts
- ✓ Lid Secured with 4 Fixings
- ✓ IP65 Rated for Indoor Use
- ✓ Integral M4 Earth Point



Product Overview

To supplement the Ampac range of addressable loop interface devices, Ampac offer a general purpose ABS plastic Ancillary Interface Enclosure.

Supports the following Ampac Loop Devices.

- ✓ 4210-0151 - Single Input Output Device
- ✓ 4210-0152 - Dual Input Output Device
- ✓ 4210-0153 - Triple Input Output Device
- ✓ 4210-0058 - Zone Interface Device

Note, screw fixings are provided with the device.

Typical Applications

- ✓ Lift Control
- ✓ Sprinkler Monitoring
- ✓ Gas Valve Shutoff
- ✓ HVAC Interface
- ✓ Aspirating Systems
- ✓ Door Control
- ✓ Beam Detectors
- ✓ Interlocks

Specifications

Material:	ABS
Dimensions:	150mm (L) x 150mm (H) x 75mm (D)
Material Thickness	1.2mm
Colour:	Cool Grey
Environmental:	IP65 (indoor applications)
Weight:	300g
Cable Knock-outs	20mm Ø - qty 5 per side

Item Numbers

4210-0034	ABS Ancillary Interface Enclosure
-----------	-----------------------------------

Fire detection and evacuation solutions that save lives.

Fixing arrangement for Ampac Interfaces

