

Fire detection and evacuation solutions that save lives.

Ancillary Interface Enclosure

- ✓ Mild Steel Enclosure
- ✓ Cable Entry Knockouts
- ✓ Supports Ampac Range of Interface Devices
- ✓ Lid Secured with 4 Fixings
- ✓ Optional Fire Alarm Interface Label
- ✓ IP Rated for Indoor Use
- ✓ 3 x Integral Wall Fixing Positions
- ✓ Integral M4 Earth Stud



Product Overview

To supplement the Ampac range of addressable loop interface devices, Ampac offer an Ancillary Interface Enclosure manufactured from Mild Steel and finished in a Surf Mist powder coating.

The Ancillary Interface Enclosure affords mechanical protection for distributed parts of a fire systems transmission devices required under AS1670.

Supports the following Ampac Loop Devices.

- ✓ 4210-0151 - Single Input Output Device
- ✓ 4210-0152 - Dual Input Output Device
- ✓ 4210-0153 - Triple Input Output Device
- ✓ 4210-0058 - Zone Interface Device

Note, screw fixings are provided with the device.

Typical Applications

- ✓ Fire Fan Controls
- ✓ Damper Controls
- ✓ Lift Control
- ✓ Sprinkler Monitoring
- ✓ HVAC Control
- ✓ Aspirating Systems
- ✓ Gas Valves
- ✓ Beam Detectors

Specifications

Material:	Mild Steel
Dimensions:	250mm (L) x 250mm (H) x 80mm (D)
Material Thickness	1.2mm
Surface Finish:	Powder Coated
Colour:	Surf Mist Ripple (Dulux)
Environmental:	IP30 (indoor applications)
Weight:	1.65kg
Cable Knock-outs	20mm Ø - qty 9 x top - 9 x bottom

Item Numbers

4210-0035	Ancillary Interface Enclosure
4210-0159	Fire Alarm Interface Label

Fire detection and evacuation solutions that save lives.

Fixing arrangement for Ampac Interfaces

