


Fire detection and evacuation solutions that save lives.

EvacU^{Elite} OEM 3094 Single Mode Dual Fibre SFP

- ✓ Used with EvacU^{Elite} Network+CPU with single mode ,dual fibre network cable
- ✓ Connects to EvacU^{Elite} NIC Ports 1&2
- ✓ Hot Pluggable SFP MSA Compliant
- ✓ Digital Optical Monitoring for Strong Diagnostic Capabilities
- ✓ Compliant to IEEE 802.3z Gigabit Ethernet
- ✓ Class 1 FDA Laser Safety and RoHS Compliant
- ✓ Max Power Consumption 1W
- ✓ FS Box –Support Real time configuration
- ✓ Cable schematic illustrated on following page



Product Overview

SFP transceiver supports up to 10km link lengths over LC duplex SMF fibre

Each SFP transceiver module is individually tested to be used on a series network interface card (NICs).

Featuring low power consumption, the 1G SFP transceiver is hot swappable


Specifications

Maximum Cable Distance	10km @SMF Using OM3 Fibre or better
Form Factor	SFP
Wavelength	1310nm-
Connector	Duplex LC
Transmitter Type	FP
DDM / DOM Support	Yes
TX Power	-9.5dBm - 3dBm
Power Consumption	<1W
Bit Error Ratio (BER)	1E-12
Temperature Rating	0 to 70°C (32 to 158°F)
Max Data Rate	1.25Gbs
Receiver Type	PIN
Receiver Sensitivity	<-20dBm
Receiver Overload	-3dBm
Extinction Ratio	>9dB
Protocols	IEEE 802.3ah-2004, IEEE 802.3z, SFF-8472, SFP MSA (INF-8074i) Compliant

Item Numbers

OEM 3094	EvacU Elite SFP Single Mode Dual Fibre 1310 nm 10km
----------	---

EvacU^{Elite} OEM 3094 Single Mode Dual Fibre SFP





AMPAC PTY LTD

Head Office - Perth

7 Ledger Road, Subiaco,

Western Australia, 6008

E: +618 9201 6100 F: +618 9201 6101

E: info@ampac.com.au W: ampac.com.au

EVACU ELITE

NETWORK CONNECTION (FIBRE)

VIA NETWORK INTERFACE CARD WITH

SFP SINGLE MODE, DUAL FIBRE MODULE

(2X OEM3094)

WIRING DIAGRAM

DRG/No. EVACU ELITE NETWORK CONNECTION (FIBRE) DWIG