



# Certificate of Conformity

Certificate num.	Registration date	Version	Valid until	
<b>afp - 3684</b>	29-Apr-2022	Number 5	Issue date 7-Apr-2026	30-Apr-2027

Page 1 of 3

## Product designation

**Redback, Model CF2050 series, type B, indoor/outdoor, bracket mount, emergency sound-system horn loudspeakers**

(Refer to the Schedule/enclosures for further specified details)

## Agent/distributor

Altronic Distributors Pty Ltd  
174 Roe Street, PERTH, WA, AUSTRALIA, 6000

## Registrant

Altronic Distributors Pty Ltd  
174 Roe Street, PERTH, WA, AUSTRALIA, 6000

### Producer

Altronic Distributors Pty Ltd  
174 Roe Street, PERTH, WA, AUSTRALIA, 6000

## Conformance criteria and evaluation

The Redback, Model CF2050 series, type B, indoor/outdoor, bracket mount, emergency sound-system horn loudspeakers has been evaluated and verified as conforming with the relevant requirements of the following criteria.

1. Australian Standard AS ISO 7240.24:2018, 'Fire detection and alarm systems - Part 24: Fire alarm loudspeakers'.

## Limitations/conditions of conformance

Limitations/conditions of conformance, where identified on this certificate, are derived from qualifications from evaluation(s) for conformity and/or other related technical documentation. All details with respect to design, assembly and installation instructions and restrictions should be checked against the producer's current technical manual/data sheets and the requirements of the Authority having Jurisdiction.

This certification is issued within the scope of CSIRO Verification Services – Rules governing ActivFire Scheme and is valid only for the product(s) as submitted for evaluation and verification of conformity, subject to the following conditions.

- Reference to details, limitations and requirements, where documented as a schedule/enclosure with this certificate.
- The Registrant is responsible for their attestation of conformity and ensuring that on-going production complies with the conformance criteria defined in this certificate.
- This certificate will not be valid if any changes or modifications are made to the product which have not been notified and validated by CSIRO Verification Services.
- This certificate is subject to periodical re-validation upon verification that all requirements, as determined by the conformity assessment body, continue to be satisfactorily met by the Registrant.
- This certificate may only be reproduced in its published form, without modification and inclusive of all schedules/enclosures.
- Any changes, errors or omissions, must be submitted in writing and if necessary or requested, substantiated with relevant evidence.
- Any representations, such as advertising or other marketing related activities or articles shall reflect the correct contents of this certificate and conform with all relevant trade practices and consumer protection legislation and regulations.
- Any terms or conditions of use as applicable to content and documentation as published or accessed through web sites administered by the CSIRO Verification Services.

Issued by

Kaj Loh  
Executive Officer – ActivFire Scheme



# Schedule to Certificate of Conformity

Certificate num.	Registration date	Version	Valid until	
<b>afp - 3684</b>	29-Apr-2022	Number 5	Issue date 7-Apr-2026	30-Apr-2027

Page 2 of 3

## Producer's description

The Redback, CF2050 series, type B, indoor/outdoor, bracket mount, emergency sound-system horn loudspeakers are intended to provide emergency warning audible broadcasts either for indoor or outdoor applications.

The Redback, CF2050 series consists of the following model variants:

- CF2050G (Grey)
- CF2050W (White)
- CF2050B (Black)

This equipment is fitted with a horn-type speaker driver and are rated for a maximum power output of 10 W when provided with an input signal of 100 Vac. Five taps are provided on the included transformer for operating at a range of output levels.

The Redback, CF2050 series, type B, indoor/outdoor, bracket mount, emergency sound-system horn loudspeakers are approximately 260 mm in length (including bracket mount), and include a plastic horn in front of the driver, with an elliptical throat approximately 189 mm across the large dimension. The loudspeakers are provided with a three-point twist-lock rear cap which is fitted with two cable glands for connection to an emergency sound system. The loudspeakers are also provided with a metal bracket for wall or ceiling mounting.

This equipment is intended for both indoor and outdoor applications

## Technical specification

The following details are a representative extract of the technical specification for the Redback, Model CF2050 series, type B, indoor/outdoor, bracket mount, emergency sound-system horn loudspeakers and may be subject to change. Complete and current details should be determined from the designated producer's technical manual/data sheets.

### Schedule of variant designations

The following is a schedule of validated variant designations of the certified/listed equipment.

Variant		Description	Colour
Type	Ident.		
Model	CF2050G	Type B, indoor/outdoor, bracket mount, emergency sound-system horn loudspeaker	Grey
	CF2050B		Black
	CF2050W		White

### Schedule of properties/characteristics

The following schedule is an extract of physical and operational properties/characteristics of the certified/listed equipment.

Rated noise power	10 Watts (100V line)
Power taps & impedance (100V line)	1.25W (8k $\Omega$ ), 2.5W (4k $\Omega$ ), 5W (2k $\Omega$ ), 7.5W (1.33k $\Omega$ ), 10W (1k $\Omega$ )
Sensitivity	104dB (1W @ 1m), 92dB (1W @ 4m) (horizontal) 103dB (1W @ 1m), 91dB (1W @ 4m) (vertical)
Maximum sound pressure level	112dB (10W @ 1m), 100dB (10W @ 4m)
Frequency response	100Hz – 12.5kHz, 500Hz – 6.3kHz $\pm$ 5dB
Coverage angle (-6dB)	500Hz: 95°, 1000Hz: 120°, 2000Hz: 90°, 4000Hz 40° (horizontal) 500Hz: 130°, 1000Hz: 130°, 2000Hz: 115°, 4000Hz 55° (vertical)
Active EQ	Not required
Environmental	Type B (for outdoor applications as per standard)
Speaker component	Aluminium voice coil former
Mounting depth	259mm
Mounting method	Wall bracket with mounting holes
Line monitoring	22 $\mu$ F bipolar capacitor
Applicable cable	2.5mm <sup>2</sup> (14AWG) max conductor area
Connection	4-way screw terminal
Finish	Flame retardant ABS (Absolac 300 MFR)
IP rating	IP66
Dimensions	189 $\varnothing$ x 259Dmm
Weight	1.4kg

# Schedule to Certificate of Conformity

Certificate num.	Registration date	Version	Valid until	
<b>afp - 3684</b>	29-Apr-2022	Number 5	Issue date 7-Apr-2026	30-Apr-2027

Page 3 of 3

## Supplementary information

### Schedule of relevant articles

The following schedule is an extract of articles significant and/or related as evidence of conformity.

Reference		Title / description	Date issued (or date validated)	Source
Ident. type	Ident.			
Report	XF3338/R4	Evaluation for Conformity of the Redback, CF2050 series, type B, bracket mount, indoor/outdoor, horn, emergency sound-system loudspeaker to the requirements of AS ISO 7240.24:2018	25-Mar-2022	CSIRO, Fire Systems Laboratory, AU
Data Sheet	CF2050	Redback Data Sheet AS ISO7240.24 10W 100V Line Horn Speaker CF2050G Grey CF2050B Black CF2050W White CF2050 Datasheet 10-11-2017.pdf	19-Oct-2021	Altronic Distributors Pty Ltd, WA, AU